


Ami *s13*



3-phase track light
Integrated power supply

- ☐ Sand White
- ☒ Black

Features



Electrical system

Total power consumption:	35 W
Power input:	100-240Vac, 50/60Hz
Operating temperature:	-10 °C ~ 35 °C
Power factor:	>0.95
Protection class:	Class II
Control protocol:	Non-DIM / Phase / 0-10V / DALI

Light source

LED type:	COB
Luminous flux:	4600 lm
Colour temperature (CCT):	2700 K / 3000 K / 4000 K
Colour rendering index (CRI):	Ra >90
Beam angle (BA):	15° / 24° / 36° / 60°

Housing

Material:	Aluminium
Weight:	x,x kg

Warranty



Period:	5 years
---------	---------

Nomenclature

Type	Series name	System power	CCT	CRI	Beam angle	Control	Colour
TL04	Ami	35 (33W)	27 (2700K)	90 (90)	15 (15°)	N (Non-Dim)	01 (Black)
			30 (3000K)		24 (24°)	P (Phase Dim)	03 (Sand White)
			40 (4000K)		36 (36°)	A (0-10V Dim)	
					60 (60°)	D (DALI-DT6)	
			TW (2700-5700K)			E (DALI-DT8)	

*Applicable model: TL0435xx90xxxxx (xx: dynamic codes)

Dimensions




Tolerance: ±2mm

Ami *S13*

Luminous intensity distribution curves


BA 15°

H (m)	En (lx)	S (sq.m)
1	26544	0,1
2	6636	0,2
3	2949	0,6
4	1659	1,0
5	1061	1,5



BA 24°

H (m)	En (lx)	S (sq.m)
1	11976	0,2
2	2994	0,7
3	1330	1,5
4	748	2,7
5	479	4,2



BA 36°

H (m)	En (lx)	S (sq.m)
1	8133	0,4
2	2033	1,6
3	903	3,5
4	508	6,2
5	325	9,7

